

## Application

Soft, double coated foam tape with 380 micron (15 mil) application thickness and differential acrylate adhesives on each side. For photopolymer plate mounting on composite and urethane sleeves or print cylinders in the flexible packaging and label printing industry (narrow- und mid web process)

## Construction

<b>Thickness without liner*</b>	approx. 430 micron (17 mil)
<b>Liner</b>	embossed PP film, 110 micron, white
<b>Adhesive, closed side</b>	acrylic
<b>Carrier</b>	soft PE foam, red on cliché side
<b>Adhesive, open side</b>	acrylic

\* average

## Product Properties

- Soft plate mounting tape
- 380 micron (15 mil) application thickness
- Hardness grade “soft” indicated by the red colour code
- Minimum thickness tolerances
- Differential acrylate with lower adhesion to cliché for a secure plate mounting without edge-lifting
- Easy and clean demounting
- Easy repositioning
- Embossed liner enables cliché mounting without air entrapments

## Application fields


- especially suitable for very fine lines, highlights and process printing
- minimum dot gain
- suitable for very fine screen count



ORAFLEX® 11392  
soft



ORAFLEX® 11393  
medium



ORAFLEX® 11394  
firm

## IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.