



As trends change, so can your walls.  
Attract attention with digitally printable,  
easy to remove wallcoverings.

VirtuWall® is a printable latex saturated wallcovering paper that can be used for a wide range of creative and promotional indoor applications. VirtuWall is easily installed on walls or other rigid surfaces. Unlike traditional painted wall murals, VirtuWall does not require a long-term commitment. Whenever you are ready for a change, remove the material and digitally print your next creative design. VirtuWall is available in both pre-pasted and non-pasted options.

**VirtuWall®** Pre-pasted

Compatible with UV inkjet, latex and true solvent printing platforms.

Activate pre-paste using a handheld pump pressure sprayer with water or consider using Zinsser® SureGrip® Activator when applying pre-pasted VirtuWall.

Dry strippable for easy removal.

**VirtuWall®** Non-pasted

Compatible with eco solvent, true solvent, UV inkjet and latex printing platforms.

Consider using Zinsser® Plus - SureGrip® Heavy Duty Clear Adhesive when applying non-pasted VirtuWall.

**Applications**

- Wall decals and décor
- Murals
- Point-of-purchase displays

**Product information**

- Printable
- Easy removal
- Buckram embossed pattern
- 10 mil. latex saturated paper

**Print Compatibility**

- Latex
- UV Inkjet
- Solvent
- Ecosolvent (Non-pasted)

Certified for  
HP Latex Inks

300+ printer profiles  
available at NEKOOSA.COM



Printed on Digital Coated 80# cover on a Ricoh C751EX

## TECHNICAL DATA ▶

	Latex	UV	Eco-Solvent
<b>Physical Properties</b>			
Caliper	215 μ (8.6 mil)	180 μ (7.2 mil)	205 μ (8.2 mil)
Weight	270 g/m <sup>2</sup>	255 g/m <sup>2</sup>	280 g/m <sup>2</sup>
Base Material	PET	PET	PET
Surface	Matte	Matte	Semi-Matte
Gloss	60 °F	≤ 3.0	≤ 5.0
	85 °F	≤ 5.0	≤ 15.0
Color/L*a*b*	85/1.0/-6.0	85/1.0/-2.0	85/1.0/-4.0
Opacity	74% ± 3	69% ± 3	70% ± 3
Fire Rating	ASTM E84 Class A	Class A	Class A

Ink Compatibility	Latex	UV	Eco-Solvent
Eco-Solvent	•		★
Solvent	•		★
Latex	★		•
UV	•	★	•
Water Based Pigmented	★		

● COMPATIBLE ★ BEST RESULTS

Roll Size	Latex	UV	Eco-Solvent
36" X 100 ft.	•		•
54" X 100 ft.	•		•
60" X 100 ft.	•		•
36" X 164 ft.		•	
54" X 164 ft.		•	
60" X 164 ft.		•	
87" X 164 ft.	•		

## GUIDELINES

### Printing Tips

Suitable printing condition: Temperature 15-30 °C (59-86 °F)/  
Relative Humidity 30-60%.

Printing on translucent media is optimized when using an ICC  
printer profile. Profiles are available at [rtape.com](http://rtape.com).

### Lamination

Lamination is optional. In order to protect image from physical  
damage and to decrease image fading, an over-laminate can be  
considered.

### Storage

Store in original packaging in a cool and dry environment.  
Temperature (10-25 °C (50-77 °F) Relative Humidity (50% RH).

### Warranty

One year from the date of purchase, with original packaging.

### Important Information

Backlit films are designed to add a wow factor to graphics. Before  
using this product, end user's shall determine the suitability for its  
intended use and application. It is the end user's responsibility to  
ensure the compliance of all laws and regulations concerning the  
use of the backlit film assumes all risk and liability therewith.